(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 20 June 2002 (20.06.2002)

PCT

(10) International Publication Number WO 02/47968 A1

(51) International Patent Classification7:

B63B 21/66

- (21) International Application Number: PCT/IB01/02499
- (22) International Filing Date:

12 December 2001 (12.12.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0030743.9

16 December 2000 (16.12.2000) GE

- (71) Applicant (for all designated States except CA. FR, US):
 WESTERN GECO SEISMIC HOLDINGS LIMITED
 [—/—]; Citco Building, P.O. Box 662, Road Town Tortola,
- (71) Applicant (for CA only): SCHLUMBERGER CANADA LIMITED [CA/CA]; 24th Floor, Monenco Place, 801 6th Avenue, SW, Calgary, Alberta T2P 3W2 (CA).


- (71) Applicant (for FR only): SERVICES PETROLIERS SCHLUMBERGER [FR/FR]; 42, rue Saint-Dominique, F-75007 Paris (FR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): KESKES, Emmanuel [FR/FR]; 20, rue Prefet Bonnefoy, F-44000 Nantes (FR). SAINT-PERE, Philippe [FR/FR]; Srpc clamant, 1, rue Henri Becquerel, BP 202, F-Clamant (FR).
- (74) Agent: STOOL, Brian, D.; WesternGeco Limited, Schlumberger House, Buckingham Gate, Gatwick, West Sussex RH6 ONZ (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,

[Continued on next page]

(54) Title: DEFLECTOR DEVICES

British Virgin Islands (VG).





(57) Abstract: A deflector device (22) for use with a tow line between a seismic survey vessel and a tow, in particular a seismic streamer or streamer array, in the water behind the vessel comprises a vertically oriented wing-shaped body (28) shaped to produce in use a sideways force which urges the tow line laterally with respect to the direction of movement of the towing vessel. The wing-shaped body (28) includes one or more buoyancy elements, and a rearwardly extending boom (32). A pivotable control surface (54) extends sideways from the boom (32), and is shaped to produce in use a force having a substantial vertical component. The angle of the control surface is remotely controllable, in order to control the depth of the deflector device.